




**NdFeB Permanent Magnets Dimensions**

**Dimensions:** mentioned in mm, can be changed.  
**Magnetisation:** standard in the direction of height (h).  
**Toleration (+/-):** standard for diameter 0,1 %; length & width 0,1%; height 0,1 mm.

CYLINDER		BLOCK			RING		
							
Diameter (D)	Height (h)	Length (l)	Width (w)	Height (h)	Outer diameter (D)	Inner diameter (d)	Height (h)
2	1	5	5	1	45	15	3
2,5	1	12	12	1,4	7	3	4
3	1,5	5	5	1,5	10	6	4
4	1,5	7	4	1,5	26	12	4
5	1,5	3	3	2	65	30	4
7	1,5	5	5	2	8	5	5
10	1,5	10	5	2	9	2,5	5
15	1,5	20	5	2	23	4	5
3	2	25	5	2	80	42	6
4	2	15	10	3	6,8	4	10
5	2	20	10	3	14	5	10
10	2	16	13	3	149	50	12,5
20	2	10	10	4	max. 100	max. 95	max. 50
4	2,5	10	10	5	min. 3	min. 1,5	min. 0,5
1,5	3	20	10	5			
2,5	3	30	11	5			
4	3	50	20	5			

7	3	10	10	6			
8	3	16	16	6			
10	3	30	16	6			
6	4	3	3	8			
8	4	10	10	10			
10	4	20	10	10			
12	4	25	25	10			
14	4	36	15	10			
5	5	42	9	10			
6	5	42	20	10			
8	5	42	42	10			
15	5	43	14	10			
18	5	63	14	10			
10	6	63	17	10			
2	8	63	28	10			
6	8	<b>63</b>	36	10			
22	8	42	20	12			
5	10	50	25	12			
21,9	10	50	24	15			
28,5	10	60	42	15			
21,9	23,5	20	18	20			
max. 100	max. 40	30	20	20			
min. 1,5	min. 0,5	50	45	25			
		60	60	20			
		60	60	40			
		max. 100	max. 95	max. 50			
		min. 3	min. 1,5	min. 0,5			

Revision: 11/2022